

VT

Pneumatic Combination Strapping Tool

For use with 16mm or 19mm Tenax® polyester strapping

High reliability and durability

For maximum uptime and a long trouble-free life

Speed

As the fastest tool in its category, the VT gets the job done more quickly and more productively

High tension

Loads will be more secure - allows operators to benefit from Tenax® polyester strap

Weld finish indicator

Tells the operator when the weld has cooled properly for maximum pack security

Unique built-in weld cool time

Guarantees a repeatable weld every time

Quick and simple

The tool is easy to remove from the package after the weld cycle

Easy to use

Simple loading and operating features make the VT very easy to learn for new operators



SIGNODE®

HANDTOOLS

PNEUMATIC



Pneumatic combination strapping tool

For use with 16mm and 19mm Tenax® polyester strapping

Design, function and operation

The VT is the fastest, highest tension pneumatic combination tool available for 16 mm and 19mm Tenax®. Strong, durable and easy to use, it is a two-button tool with one button for tensioning and one for sealing.

Providing tension in excess of 3600 N at very high speed, the VT is the fastest in its category. Its two-button operation, fast take-up speed and dialled in weld cool time offer the maximum productivity available. These innovative features also mean loads will be more secure and enable more applications to benefit from the properties of Tenax® polyester strap.

Designed to be the most durable tool in its class, the VT offers low operating costs combined with excellent durability. Its superb reliability delivers greater uptime – while the longer lasting parts ensure maximum service life with minimal maintenance demands.

The VT is the only tool of its kind to offer an automatic weld facility. A weld cool finish indicator tells the operator when the weld has cooled properly. Additionally the tool cannot be removed from the strap until the joint has cooled down sufficiently which ensures consistent weld strength resulting in more secure loads. The weld cool time indicator eliminates guessing or counting by the operator, and the VT provides a repeatable weld quality every time.

Easy operation is a key feature of the VT, which is the lightest in weight of any tool in its category. Features such as the two-strap loading, two-button operation, positive strap cut-off and the weld cool indicator make it as simple as possible for new operators.

Specification

Joint type	Friction weld
Tension Range	up to 3600 N
Operational pressure	maximum: 6.2 Bar minimum: 5.7 Bar
Air consumption	13.4 M ³ /Hr
Weight	4.2 Kg
Dimensions L x W x H	260mm x 135mm x 110mm
Strap	
Material	Polyester
Width	16 - 19mm
Gauge	up to 1.4mm

Weld cool time indicator

A unique weld cool time indicator means the tool will provide a repeatable weld every time – with no guessing or counting needed.



Two button operation

The simple two-button design means no extensive training is needed by operators before use.



High speed, high tension

The VT provides tension in excess of 3600 N and offers the fastest operation in its category.



Easy loading

Two straps at a time can be loaded for quicker operation and greater productivity.



Durable, robust construction

With its tough metal construction and long-lasting parts, the tool ensure maximum uptime and high durability.



Easy tool removal

At the end of the strapping cycle, a de-blocking mechanism releases strap tension, enabling the tool to be easily removed from the pack.

