

# 5FRM

## Fully automatic random case sealer with four flap closure



New Flexible 'Soft' taping head with Variable tape overlap up to 75mm



Optional No/ Low Tape indicator reduces changeover downtime



Optional MS/ Polycarbonate Safety Guards for Operator's safety.

### Features and benefits

- Automatic sealing of random size cartons
- Machine automatically adjust itself to varying carton sizes
- Independently controlled top and side drives ensures smooth flow of cartons
- Ideal for integrating with different production lines
- Auto on /off feature enables power saving during idle time
- Twin mast column for greater stability during operation
- Pneumatically controlled top drive and side guides align with The carton width and height automatically
- Uniform and controlled pressure during taping
- Belt speed of 18 m/minute as per international norms
- Optional MS(Wiremesh) or Polycarbonate safety guards for operator safety.

# 5FRM

## Fully automatic random case sealer with four flap closure

### Technical specifications

Machine specification	5FRM-Standard	5FRM-Small
Taping Head Type	Flexible-2"/2.5"/3"	Flexible-2"/2.5"/3"
Length	2040 mm	1470 mm
Width	960 mm	700 mm
Height	1450 mm	1350 mm
Weight	295 Kg	255 Kg
Color	RAL 6000 & RAL 1021 Yellow (Moving Parts)	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive Motor	0.25 HP, 3 No.	0.25 HP, 3 No.
Machine Through put	5-7 carton/min	8-9 carton/min
<b>Utility requirements</b>		
Air requirement	6 Bar	6 Bar
Air consumption	15.8 Litres/ Cycle	8.6 Litres/Cycle
Power supply	415 V AC, 3 Phase, 50 Hz	415 V AC, 3 Phase, 50 Hz
Power consumption	0.6 KW	0.4 KW
Tap Roll length	65 M/ 650 M/ 1000 M	65 M/ 650 M/ 1000 M
<b>Case dimension</b>		
Length	200- 570 mm	200- 400 mm
Width	170-450 mm	130-320 mm
Height	150-400 mm	130-310 mm
Weight	7-40Kg	7-40Kg
Carton ply	5 Ply	5 Ply

 **SIGNODE**<sup>®</sup>

Your partner in industrial packaging world wide

**E** : [info@signodeindia.com](mailto:info@signodeindia.com)

**W** : [www.signodeindia.com](http://www.signodeindia.com)

Toll Free Number for Services 1800 419 1466