
6AM

Heavy duty case sealer for tall and heavy cartons





Features and benefits

- Ideal for batch production of tall and heavy cartons
- Twin mast column for greater stability during operation
- Separate top and bottom Drive for perfect taping
- 3" drive belts for maximum load carrying capacity
- Uniform and controlled pressure during taping.
- Twin flap squeeze rollers provides additional squeezing for perfect top flap alignment.
- Belt speed of 20 m/minute as per international norms
- Inbuilt tool box for ease of maintenance.
- Self-centering side guides for accurate centering

- Positive top and bottom drive to ensure sealing of tall and heavy cartons, in addition to regular cartons
- Telescopic legs for height adjustment
- Quick and simple adjustment for varying carton sizes.
- Optional MS/polycarbonate Safety Guards with/ without electrical interlock for operational safety.





Heavy duty case sealer for tall and heavy cartons

Machine Specification		6AM
Taping Head Flexible	:	(2"/2.5"/3")
Length	:	1030 mm
Width	:	826 mm
Height	:	1650 mm
Weight	:	198 Kg
Color	:	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive motor		0.25 HP, 3 No.
Belt speed	:	18 Metres/ Min
Machine through put	:	Belt speed/(Carton length+280 mm)
Utility requirements		
Air requirement	:	NA
Air consumption	:	NA
Air consumption Power supply	:	NA 415 V AC, 3 Phase, 50 Hz
Power supply	:	
	: : :	415 V AC, 3 Phase, 50 Hz
Power supply Power consumption Tap roll length	: : :	415 V AC, 3 Phase, 50 Hz 0. 4 KW
Power supply Power consumption	: : : :	415 V AC, 3 Phase, 50 Hz 0. 4 KW
Power supply Power consumption Tap roll length Case dimensions Length	: : : :	415 V AC, 3 Phase, 50 Hz 0. 4 KW 65 M / 650 M/ 1000 M
Power supply Power consumption Tap roll length Case dimensions	: : : :	415 V AC, 3 Phase, 50 Hz 0. 4 KW 65 M / 650 M/ 1000 M 150 mm - Un Limited



E : info@signodeindia.comW : www.signodeindia.com



Toll Free Number for Services 1800 419 1466